

# Special tools "C" shape forming pliers

## PNR 30 D




**PNR 30 D:** Special forming tool that C shapes the component wire. Bent at 45°.  
Steel thickness 3mm. Tool length 145mm.

ESD-safe handles.

技术咨询与报价

电话: 18823303057 QQ:2104028976



| Order code | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|------------|-------------|--------------------|--------------------|-------------------|
| PNR 30 D   | 145         | 3                  | 1.02               | 18                |


## PNG 5000 D



**PNG 5000 D:** Special tool for the forming of components in a C shape. Its special radius enables components to be formed with no stress.

Steel thickness 5mm. Tool length 150mm.

ESD-safe handles



| Order code | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|------------|-------------|--------------------|--------------------|-------------------|
| PNG 5000 D | 150         | 3                  | 1.02               | 18                |



## PNR 5000 D



**PNR 5000 D:** A special tool that cuts and forms the component wire in one operation. Length setting is carried out by means of a sliding stop (A min 4 max 16).

Steel thickness 5.0mm. Tool length 150mm.

ESD-safe handles



| Order code | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|------------|-------------|--------------------|--------------------|-------------------|
| PNR 5000 D | 150         | 3                  | 1.02               | 18                |



## PNR 5010 D



**PNR 5010 D:** Forming pliers that cuts and forms in a double opposite C shape the component wire in one operation. Length setting is carried out by means of a sliding stop (A min 4 max 16).

Steel thickness 10mm. Tool length 150mm.

ESD-safe handles



| Order code | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|------------|-------------|--------------------|--------------------|-------------------|
| PNR 5010 D | 150         | 3                  | 1.02               | 18                |



## PTR 30 C D



**PTR 30 CD:** Pliers which forms the component wire in a C shape and cuts off the residual part. Residual component lead's length 3mm.

Steel thickness 3.0mm. Tool length 150mm.

ESD-safe handles



| Order code | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|------------|-------------|--------------------|--------------------|-------------------|
| PTR 30 CD  | 150         | 3                  | 1.02               | 18                |



## PTR 30 C/5D



**PTR 30 C/5D:** Pliers which forms the component wire in a C shape and cuts off the residual part. Residual component lead's length 4mm.

Steel thickness 3.0mm. Tool length 150mm.

ESD-safe handles



| Order code  | Lenght (mm) | Cutting force (kg) | Copper wire (Ø mm) | Copper wire (awg) |
|-------------|-------------|--------------------|--------------------|-------------------|
| PTR 30 C/5D | 150         | 3                  | 1.02               | 18                |