

# 瑞士环球Sipel不锈钢精密尖头镊子

Six Grades Available

BIO-MED, Suffix /BM  
BIO-TECH, Suffix /T  
ZENITH, Suffix /S  
Example: AA-SA/T

Stainless Antiacid Antimagnetic Steel

PREMIUM, Suffix /E  
PRIME-X, Suffix /P  
SL PRIME-X, Prefix SL...



|                                                        |                 |                       |  |
|--------------------------------------------------------|-----------------|-----------------------|--|
| <b>A-SA</b><br>-Fine Straight                          | 115 mm – 4 1/2" | <br>* 0.40mm - .0157" |  |
| <b>AA-NI</b><br>-Fine Strong Tips<br>-Nickel Plated    | 125 mm – 5"     | <br>* 0.40mm - .0157" |  |
| <b>AA-SA</b><br>-Fine Strong Tips                      | 125 mm – 5"     | <br>* 0.40mm - .0157" |  |
| <b>AC-SA</b><br>-Fine Strong Tips                      | 110 mm – 4 1/4" | <br>* 0.30mm - .012"  |  |
| <b>GG-SA</b><br>-Very Fine Tips                        | 125 mm – 5"     | <br>* 0.40mm - .0157" |  |
| <b>HH-NI</b><br>-Strong Tips<br>-Nickel Plated         | 110 mm – 4 1/4" | <br>* 0.40mm - .0157" |  |
| <b>MM-NI</b><br>-Strong Multipurpose<br>-Nickel Plated | 125 mm – 5"     | <br>* 0.50mm - .020"  |  |
| <b>MM-SA</b><br>-Strong Multipurpose                   | 125 mm – 5"     | <br>* 0.50mm - .020"  |  |
| <b>NN-NI</b><br>-Fine Tips<br>-Nickel Plated           | 125 mm – 5"     | <br>* 0.50mm - .020"  |  |

技术咨询与报价

电话: 18823303057 QQ:2104028976

**O-SA**

120 mm – 4<sup>3</sup>/<sub>4</sub>"

-Fine Straight Strong Tips



\* 0.40mm - .0157"



**OC-SA**

90 mm – 3<sup>9</sup>/<sub>16</sub>"

-Strong Short Tips



\* 0.40mm - .0157"



**OC10-SA**

100 mm – 4"

**OC11-SA**

110 mm – 4<sup>1</sup>/<sub>4</sub>"

技术咨询与报价

电话: 18823303057 QQ:2104028976

**OO-SA尖头镊子**

120 mm – 4<sup>3</sup>/<sub>4</sub>"

-Strong Thick Tips



\* 0.40mm - .0157"



**OO-NI**

115 mm – 4<sup>1</sup>/<sub>2</sub>"

-Fine Tips

-Nickel Plated



\* 0.30mm - .012"



**OOB-SA**

120 mm – 4<sup>3</sup>/<sub>4</sub>"

- Fine Straight Strong Tips



\* 0.40mm - .0157"



**OOD-SA带齿镊子**

120 mm – 4<sup>3</sup>/<sub>4</sub>"

-Strong Thick Serrated Tips



\* 0.40mm - .0157"



**OOO-SA**

120 mm – 4<sup>3</sup>/<sub>4</sub>"

-Strong Thick Rounded Tips



\* 0.30mm - .012"



**PSF-SA**

130 mm – 5<sup>1</sup>/<sub>8</sub>"

-Flat Square Tips



\* 2.30mm - .090"

