

STEEL TWEEZERS

Stainless Antiacid Antimagnetic Steel



Switzerland

Six Grades Available

BIO-MED, Suffix /BM

BIO-TECH, Suffix /T

ZENITH, Suffix /S

PREMIUM, Suffix /E

PRIME-X, Suffix /P

SL PRIME-X, Prefix SL...

Example: 231-SA/E

218-SA 160 mm – 6 1/4"

-With Alignment Pin
-Diamond Style, Fine Tips



* 0.60mm - .0235"



219-SA 160 mm – 6 1/4"

-With Alignment Pin
-Diamond Style, Medium Tips



* 0.80mm - .032"



220-SA 140 mm – 5 1/2"

-With Alignment Pin
-Diamond Style, Medium Tips



* 0.90mm - .035"



220C-SA 140 mm – 5 1/2"

-With Alignment Pin
-Diamond Style, Medium Bent Tips



* 0.90mm - .035"



227-SA 140 mm – 5 1/2"

-Diamond Style, Medium Tips
-Slide Lock



* 1.00mm - .0394"



231-SA 120 mm – 4 3/4"

-Fine Straight Tips



* 0.60mm - .0235"



231A-SA 120 mm – 4 3/4"

-Fine Straight Serrated Tips



* 0.60mm - .0235"



245-SA 145 mm – 5 3/4"

-Strong Serrated Tips




* 3.50mm - .137"



251A-SA 165 mm – 6 1/2"

-Long Flat Rounded End Tips



* 6.00mm - .235"



Other Models Available Upon Request

STEEL TWEEZERS

Six Grades Available

BIO-MED, Suffix /BM
BIO-TECH, Suffix /T
ZENITH, Suffix /S
Example: 35A-SA/S

Stainless Antiacid Antimagnetic Steel

PREMIUM, Suffix /E
PRIME-X, Suffix /P
SL PRIME-X, Prefix SL...



Switzerland

34-SA

120 mm – 4³/₄"

-Flat Straight Tips



* 3.00mm - .118"



34A-SA

120 mm – 4³/₄"

-Flat Straight Tips



* 6.50mm - .256"



34B-SA

120 mm – 4³/₄"

-Flat Angled Tips



* 2.50mm - .098"



34B-SA-M

120 mm – 4³/₄"

-Flat Angled Tips



* 3.50mm - .14"



35A-SA

120 mm – 4³/₄"

-For Handling Delicate Electronics Parts



* 6.00mm - .235"



35B-SA

120 mm – 4³/₄"

-Small Curved Tips



* 1.40mm - .055"



35AD-SA

120 mm – 4³/₄"

-Fine Straight Serrated Tips



* 6.00mm - .235"



36A-SA

120 mm – 4³/₄"

-Flat Angled Tips



* 6.00mm - .235"



STEEL TWEEZERS

Stainless Antiacid Antimagnetic Steel



Switzerland

Six Grades Available

BIO-MED, Suffix /BM

BIO-TECH, Suffix /T

ZENITH, Suffix /S

Example: 51-SA/BM

PREMIUM, Suffix /E


PRIME-X, Suffix /P

SL PRIME-X, Prefix SL...

36A-SA-R

120 mm – 4³/₄"

-Flat Angled Round End Tips




* 6.00mm - .235"



38-SA

110 mm – 4¹/₄"

-Excellent For Pick Up Miniature Round Wire




* 1.00mm - .0394"



39-SA

110 mm – 4¹/₄"

-Excellent For Pick Up Miniature Round Wire




* 1.00mm - .0394"



40-SA

110 mm – 4¹/₄"

-Excellent For Pick Up Miniature Round Wire




* 1.00mm - .0394"



47-SA

135 mm – 5¹/₄"

-Strong Flat Square Tips, Very Popular



A = 0.85mm - .0335" B = 0.20mm - .0078"



51-SA

115 mm – 4¹/₂"

-Superfine Bent Tips



* 0.20mm - .0078"



52A-SA

120 mm – 4³/₄"

-Flat Tips
-Smooth Action



* 2.00mm - .078"




64-SA

115 mm – 4¹/₂"

-Very Fine Tweezer



* 0.40mm - .0157"



65A-SA

140 mm – 5¹/₂"

-Very Fine Bent Tips



* 0.30mm - .012"

